



EPS BOX PRO-HC

THREE-PHASE



- PC, Robust metal enclosure IP65
- Applied to residential, commercial solar installations
- Compatible with AIO-H3/H3/H3 Smart/P3-S/H3 Pro/P3 Pro inverter
- Automatically switch to On-Grid/Off-Grid state



Max. input
current
(per phase) 63A



Safety



IP65
Rated



Easy
Installation



For more information about the Fox ESS range, visit:
www.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	EPS BOX PRO-HC
UTILITY SUPPLY	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
Rated Frequency [Hz]	50 / 60
Max. Input Current (Per Phase) [A]	63
INVERTER GRID	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
Rated Frequency [Hz]	50 / 60
Max. Input Current (Per Phase) [A]	63
INVERTER EPS	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
Rated Frequency [Hz]	50 / 60
Max. Input Current (Per Phase) [A]	63
LOAD	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
Rated Frequency [Hz]	50 / 60
Max. Output Current (Per Phase) [A]	63
COMMUNICATION INTERFACE	
RS-485	Meter
GENERAL DATA	
Cooling Concept	Natural
Installation	Wall-mounted
Operating Temperature Range [°C]	-25 ~ +60 (Derating at 45)
Dimensions (W*H*D) [mm]	550 * 420 * 138.5
Dimensions of packing (W*H*D) [mm]	660 * 515 * 235
Net Weight [kg]	17
Gross Weight [kg]	18
Ingress Protection	IP65